

Serial No. 10/705,753
Response dated March 4, 2005
Reply to Office Action of Dec. 2, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1-57. (Canceled)

58. (New) An apparatus for removing a contaminant from an atmosphere in an airplane cabin, the apparatus comprising:

- (a) an adsorptive element comprising a body having a thickness of at least 1 cm and comprising a plurality of passages extending therethrough in a side-by-side array, the passages having a cross-sectional width no greater than about 5 mm, the element comprising a coating less than about 0.5 mm thick substantially covering the passages, the coating comprising a polymeric binder and an adsorptive particulate and having only incidental catalytic activity; and
- (b) a housing having an inlet, an outlet, a receiving volume for the adsorptive element, each of the inlet and outlet in air flow communication with the passages of the adsorptive element.

59. (New) The apparatus according to claim 58 comprising at least three adsorptive elements.

60. (New) A system for removing a contaminant from a gas stream for an airplane cabin, the system comprising.

- (a) an adsorptive article comprising:
 - (i) a body having a thickness of at least 1 cm and having a plurality of passages extending along the thickness, the passages having an interior surface and a cross-sectional width of no more than 5 mm; the passages defining an inlet of the article and an outlet; and

Serial No. 10/705.753

Response dated March 4, 2005

Reply to Office Action of Dec. 2, 2004

- (ii) a coating present on the interior surface of the passages, the coating comprising a polymeric binder and an adsorbent particulate and having a thickness less than 0.5 mm, the coating being substantially free of catalytic activity; and
- (b) a particulate filter in air flow communication with the inlet of the adsorptive article.

61. (New) The system according to claim 60, wherein the interior surface of the passages has an exposed surface area of about 250 cm² to 10 m².

62. (New) The system according to claim 60, wherein the adsorptive article is configured to remove VOCs from the gas stream.

63. (New) A method of removing a contaminant from a gas in an airplane cabin, the method comprising:

- (a) installing a contaminant removal article in a pathway of the gas, the article comprising a body having a thickness of at least 1 cm, the body comprising a plurality of passages extending through the body in a side-by-side array, the passages having a cross-sectional width of no more than about 5 mm, the passages having an interior surface and a coating substantially covering the interior surface, the coating comprising a polymeric binder and an adsorptive particulate, the coating having a thickness of no more than 0.5 mm, and the article having only incidental catalytic properties;
- (b) contacting the gas with the article, the gas having contaminant present at a level of 50 ppm-volume to 2 ppb-volume; and
- (c) removing at least 90% of the contaminant from the gas with a pressure drop of no greater than 1 inch water at an airflow filter face velocity of 0.5 m/s.

Serial No. 10/705,753

Response dated March 4, 2005

Reply to Office Action of Dec. 2, 2004

64. (New) The method according to claim 63, wherein the step of removing comprises:
- (a) removing at least 95% of the contaminant from the gas with a pressure drop of no greater than 1 inch water at an airflow filter face velocity of 0.5 m/s.
65. (New) The method according to claim 63, wherein the step of removing comprises:
- (a) removing at least 98% of the contaminant from the gas with a pressure drop of no greater than 1 inch water at an airflow filter face velocity of 0.5 m/s.
66. (New) The method according to claim 63, wherein the step of removing comprises:
- (a) removing at least 90% of the contaminant from the gas with a pressure drop of no greater than 0.5 inch water at an airflow filter face velocity of 0.5 m/s.
67. (New) The method according to claim 63, wherein the step of removing comprises:
- (a) removing at least 90% of the contaminant from the gas with a pressure drop of no greater than 0.1 inch water at an airflow filter face velocity of 0.5 m/s.
68. (New) The method according to claim 63, wherein the step of contacting a gas with the article comprises:
- (a) contacting the gas with the article, the gas having VOCs present at a level of 50 ppm-volume to 2 ppb-volume.